

TÔLES



■ Egalement disponible en décapé
DD II (ST W 22)
EN 10051

TOLES LAMINEES A CHAUD

S235 JRG2 (ST 37-2)

EN 10051

Epaisseur (mm)	Poids (Kg / tôle)				
	Dimensions (mm)				
	2000 * 1000	2500 * 1250	3000 * 1500	6000 * 1500	6000 * 2000
1,5	24,0		54,0		
2	32,0	50,0	72,0		
2,5	40,0	62,5	90,0		
3	48,0 [■]	75,0	108,0	216,0	288,0
4	64,0 [■]	100,0 [■]	144,0		384,0
5	80,0 [■]	125,0 [■]	180,0		480,0
6	96,0	150,0	216,0		576,0
8	128,0	200,0	288,0		768,0
10	160,0	250,0	360,0		960,0
12	192,0	300,0	432,0		1152,0
15	240,0	375,0	540,0		1440,0
20	320,0	500,0	720,0		1920,0
25	400,0	625,0	900,0		
30	480,0	750,0	1080,0		
35	560,0	875,0	1260,0		
40	640,0	1000,0	1440,0		
50	800,0	1250,0	1800,0		
60	960,0	1500,0	2160,0		

Formats spéciaux pour la fabrication de citernes (Stock permanent)

	Dimensions (mm)			
	1250 * 1000	2000 * 1250	2000 * 1500	2500 * 1000
3	30,0	60,0	72,0	60,0